WELLS CARGO®

FASTTRAC® 8.5' WIDE
THE ALL PURPOSE TRAILER

VALUE-DRIVEN
WITH A SPIRIT THAT'S BORN TO HAUL!

The FastTrac® brings a whole new level of value to the light-duty recreational cargo trailer market. A balanced combination of versatility and affordability, the FastTrac® delivers on all fronts. From its unpretentious styling to its uncompromising dependability, only Wells Cargo® could pack so much value into an entry-level trailer.

Trailer shown features Deluxe Package available at an additional charge.

FASTTRAC®

SPECIFICATIONS

FAST TRAC

		FT85162	FT85202	FT85242
Body:	**Length**	18' 0"	22' 0"	26' 0"
	Width	8' 4"	8' 4"	8' 4"
Overall:	**Length**	20' 0"	24'0"	28' 0"
	Width	8' 6"	8' 6"	8' 6"
	Height	8' 3"	8' 3"	8' 3"
Interior:	**Length**	17' 9"	21' 9"	25' 9"
	Width	8' 1"	8' 1"	8' 1"
	Height	6' 6"	6' 6"	6' 6"
Width Between Wheel Wells		83"	83"	83"
Platform Height		20"	20"	20"
Spring Suspension E-Z Lube® Axles: Qty		Tandem	Tandem	Tandem
Total Axle Capacity		7,000 lbs.	7,000 lbs.	7,000 lbs.
Electric Brakes with Breakaway Kit		Electric Drum	Electric Drum	Electric Drum
Radial Tire Size		ST205/75R15	ST205/75R15	ST205/75R15
Tire Load Range		C	C	C
Hitch Ball Size		2-5/16"	2-5/16"	2-5/16"
Hitch Height to Top of Ball		19"	19"	19"
Hitch Weight (% of Curb Weight)		10% to 15%	10% to 15%	10% to 15%
Curb Weight (Approximate)		2,485 lbs.	2,975 lbs.	3,465 lbs.
GVWR		7,000 lbs.	7,000 lbs.	7,000 lbs.
Payload Capacity (Approximate)		4,515 lbs.	4,025 lbs.	3,535 lbs.
Rear Ramp Door Opening - Width x HeightSpoke		94" x 72"	94" x 72"	94" x 72"
Side Door Opening - Width x Height		32" x 72"	32" x 72"	32" x 72"
12v Trailer End Connector		7-way	7-way	7-way
Tube Main Rails		2" x 6"	2" x 6"	2" x 6"

STANDARD FEATURES

- 15” Radial Tires with Silver Spoke Wheels
- Smooth Aluminum Radius Fenderettes
- .080 Aluminum Composite Panels *(Select Colors)*
- 1-Piece Aluminum Roof
- Semi-Screwless Exterior (Screws on Seams only)
- 12v LED Exterior Lighting *(New LazerMax exclusive clearance light)*
- 12v LED Slim Line Tail Lights
- 16” Starbright Stoneguard
- Flow-Thru Sidewall Vents
- Rear Ramp Door with Spring Assist & 16” Ramp Extension
- 32” Side Door with Bar Lock
- 12v Dome Light with Self-Switch
- 3/8" High PerformancePlexCore™ Sidewall Liner
- 3/4” High Performance PlexCore™ Decking
- 500 lb. Surface Wall Mounted Rope Rings (4)
- Spring Axles with 4” Drop
- E-Z Lube® Hubs
- Electric Brakes with Breakaway Kit
- Undercoated Chassis
- 16” OC Vertical Posts
- 16” OC Crossmembers
- 24” OC Tube Roof Bows
- 1-Year Limited Warranty

Standard Exterior - Semi-Screwless .080 ACP

Standard Interior Shown

AMERICAN CARGO GROUP

www.wellscargo.com

Wells Cargo reserves the right to change or alter any specification, feature, option, package and/or pricing **without** notice. Some trailers are shown with optional equipment available at additional charge. See your authorized Wells Cargo dealer for more Information.

©Wells Cargo® 2026 Form WC_FT_85_FLYER_0526