



**WELLS
CARGO®**

MOTORTRAC® RACE GOOSENECK

OUR FLAGSHIP MOTORSPORTS TRAILER

PERFORMANCE THAT'S TRUE TO FORM!

The MotorTrac® GOOSENECK Race Trailer from Wells Cargo® is all about delivering performance.

Performance on the road . . .

Performance at the track . . .

Performance year after year.

Racers who live for results choose equipment that keeps pace with their ambition. That's why the MotorTrac® GOOSENECK stands as the flagship, delivering uncompromising strength, relentless reliability, and inspiring confidence where it matters most.



Trailers shown may feature optional equipment available at an additional charge.

MOTORTRAC

SPECIFICATIONS

		MTG8524T4	MTG8528T4	MTG8532T4	MTG8536T5	MTG8540R4	MTG8544R4
Body:	Length	24'0"	28'0"	32'0"	36'0"	40'0"	44'0"
	Width	8'4"	8'4"	8'4"	8'4"	8'4"	8'4"
Overall:	Length	24'0"	28'0"	32'0"	36'0"	40'0"	44'0"
	Width	8'6"	8'6"	8'6"	8'6"	8'6"	8'6"
	Height (to top of roof vent)	9'2"	9'2"	9'2"	9'2"	9'2"	9'2"
Interior:	Width	8'0"	8'0"	8'0"	8'0"	8'0"	8'0"
Interior:	Length - Lower Deck	15'9"	19'9"	23'9"	27'9"	31'9"	35'9"
	Length - Upper Deck	8'0"	8'0"	8'0"	8'0"	8'0"	8'0"
Interior:	Height - Lower Deck	6'10"	6'10"	6'10"	6'10"	6'10"	6'10"
	Height - Upper Deck	31"	31"	31"	31"	31"	31"
Width Between Wheel Boxes		83"	83"	83"	83"	83"	83"
Height of Wheel Box from Floor		9-3/4"	9-3/4"	9-3/4"	9-3/4"	9-3/4"	9-3/4"
Platform Height at Beavertail		21"	21"	21"	21"	21"	21"
Torflex® Suspension E-Z Lube® Axles: Qty		Tandem	Tandem	Tandem	Tandem	Triple	Triple
Electric Brakes with Breakaway Kit		Electric Drum	Electric Drum	Electric Drum	Electric Drum	Electric Drum	Electric Drum
Radial Tire Size		ST235/85R16	ST235/85R16	ST235/85R16	ST235/85R16	ST235/85R16	ST235/85R16
Tire Load Range		E	E	E	E	E	E
Gooseneck Ground Clearance (Approximate)		~ 64"	~ 64"	~ 64"	~ 64"	~ 64"	~ 64"
Hitch Height to Top of Ball (Approximate)		~ 41"	~ 41"	~ 41"	~ 41"	~ 41"	~ 41"
GVWR		12,000 lb.	12,000 lb.	12,000 lb.	14,000 lb.	18,000 lb.	18,000 lb.
Curb Weight		5,520 lb.	6,020 lb.	6,520 lb.	7,120 lb.	9,300 lb.	10,025 lb.
Payload Capacity (Estimated *)		6,480 lb.	5,980 lb.	5,480 lb.	6,880 lb.	8,700 lb.	7,975 lb.
Rear Ramp Door Opening - Width x Height		96" x 78"	96" x 78"	96" x 78"	96" x 78"	96" x 78"	96" x 78"
12v Male Connection		7-way	7-way	7-way	7-way	7-way	7-way
Tube Main Rails		3" x 8"	3" x 8"	3" x 8"	3" x 8"	3" x 8"	3" x 8"

STANDARD FEATURES

- 2⁵/₁₆" Adjustable Round Gooseneck Ball Coupler — 25,000 lb.
- .080 ACP Panels, Bonded for Smooth Appearance (*Select Colors*)
- Cast Aluminum Corners (Front & Rear)
- Stainless Steel Cap and Front Corners
- Polished Aluminum Rear Corners & Header
- 5,000 lb. Square D-Rings with Welded Plates (4)
- Spring-Assisted Rear Ramp Door with Ramp Extension
- Heavy-Duty Locking Paddle Latch on Rear Ramp Door
- Economy Line Ceiling Liner
- 3/4" PlexCore Decking
- 3/8" PlexCore Sidewall Liner
- Dust-Resistant Frame Design
- Vertical Tube Posts 16" On Center
- Spread Torflex® Axles with Drop Skirting
- Goodyear® Radial Tires with Black Aluminum Wheels
- LED Amber Clearance Front 3 Light Center Cluster
- Angled ATP Stoneguard & Enclosed Gooseneck Underbelly
- 36" x 78" Side Entry Door with Recessed Step
- 14" x 14" Non-Powered Roof Vent (2)
- Breakaway Assembly Kit with Charger
- 12V Dome Lights (4)
- LED Exterior Lighting with Smoked Lens
- Beavertail — Length Varies by model
- 8' Upper Deck
- Double Leg Manual 2 Speed Landing Gear
- 3-Year Limited Warranty



Turbo package with additional optional equipment available at additional cost.