WELLS CARGO®

ROAD FORCE® V-FRONT AUTO
THE SMART CHOICE

BEYOND THE STANDARD

Unlike the other models in the Road Force® line-up, the 8.5' wide V-front is an auto hauler at heart. If you're a collector or racer looking for superior quality, durability and style, then the 8.5' wide Road Force® V-front is a smart choice. For starters, the Road Force® features a bonded exterior, an extra wide 94" rear ramp door opening, no-show beavertail, side entry door with recessed step, sidewall vents and tie-down rings - all standard. Factor in the radial tires, LED slim line tail lights, ArmorTech™ Covered A-Frame and a 3-year limited warranty; now you know you've got a trailer that's packed with value and built to last!

Trailer shown may feature optional equipment available at an additional charge.

ROAD FORCE®

V-FRONT

SPECIFICATIONS

ROAD FORCE®

V-FRONT

		RFV8516T2	RFV8520T2	RFV8524T2	RFV8528T3
Body:	**Length**	17' 10"	20' 9"	24' 9"	29' 10"
	Width	8' 4"	8' 4"	8' 4"	8' 4"
Overall:	**Length**	19' 6"	23' 6"	27' 6"	31' 6"
	Width	8' 6"	8' 6"	8' 6"	8' 6"
	Height	8' 7"	8' 7"	8' 7"	8' 7"
Interior:	**Length (Includes "V")**	17' 6"	21' 6"	25' 6"	29' 6"
	Width	8' 0"	8' 0"	8' 0"	8' 0"
	Height	6' 6"	6' 6"	6' 6"	6' 6"
Platform Height		17"	17"	17"	18"
Spring Suspension E-Z Lube® Axles: Qty		Tandem	Tandem	Tandem	Tandem
Total Axle Capacity		7,000 lbs.	7,000 lbs.	7,000 lbs.	10,400 lbs.
Brakes with Breakaway Kit		Electric Drum	Electric Drum	Electric Drum	Electric Drum
Radial Tire Size		ST205/75R15	ST205/75R15	ST205/75R15	ST225/75R15
Tire Load Range		C	C	C	D
Hitch Ball Size		2-5/16"	2-5/16"	2-5/16"	2-5/16"
Hitch Height to Top of Ball		20"	20"	20"	21"
Hitch Weight (% of Curb Weight)		10% to 15%	10% to 15%	10% to 15%	10% to 15%
Curb Weight (Approximate)		2,580 lbs.	3,220 lbs.	3,860 lbs.	4,680 lbs.
GVWR		7,000 lbs.	7,000 lbs.	7,000 lbs.	9,990 lbs.
Payload Capacity (Approximate)		4,420 lbs.	3,780 lbs.	3,140 lbs.	5,310 lbs.
Rear Ramp Door Opening - Width x Height		94" X 72"	94" X 75"	94" X 75"	94" X 75"
12v Male Connection		7-way	7-way	7-way	7-way
Beavertail		Optional 24"	48"	48"	48"

STANDARD FEATURES

- Exclusive Bull Nose Profile
- 15" Radial Tires with Silver Spoke Wheels
- Smooth Aluminum Fenderettes
- .080 ACP Panels *(Select Colors)*
- .080 Aluminum Roof Cove
- 1-Piece Aluminum Roof
- 12v LED Slim Line Tail Lights
- 12v LED Clearance Lights *(New LazerMax Exclusive Clearance Light)*
- 24" ATP Stoneguard
- Flow-Thru Sidewall Vents
- Rear Ramp Door with Spring Assist
- 16" Ramp Extension
- 36" Side Entry Door with Flush Lock
- Recessed Step at Side Door
- 12v LED Dome Light with Wall Switch (2)
- 3/4" PlexCore™ Decking
- 3/8" PlexCore™ Sidewall Liner
- 5,000 lb. Square D-Rings with Welded Plate (4)
- Spring Axles with E-Z Lube® Hubs
- Electric Brakes with Breakaway Kit
- 2" x 6" Tube Main Rails *(2" x 8" on select larger models)*
- Entire Chassis Undercoated
- ArmorTech™ on A-Frame and Rear End Rail
- 16" OC Tube Vertical Posts
- 16" OC Crossmembers
- 16" OC Tube Roof Bows
- 3-Year Limited Warranty

Trailers shown may feature optional equipment available at additional cost.

AMERICAN CARGO GROUP

www.wellscargo.com

Specifications, features, options, packages & pricing subject to change **without** notice. See your authorized Wells Cargo® dealer for more information.

©Wells Cargo® 2025 Form WC_RFV85_FLYER_0723