

**WELLS  
CARGO®**

# THE ALL NEW STEEL SPORTTRAC™



Trailers shown may feature optional equipment available at an additional charge.

The new Wells Cargo® steel SportTrac mid-deck is your no limits trailer for all your powersport toys. An all-steel frame offers plenty of strength and long-lasting durability. Ramp doors, front & rear, for quick takeoffs on arrival and easy loading when heading back home. The mid-deck platform height is a hybrid design with drive over wheel boxes. Perfect for all your off-road throttle machines.

# **SPORTTRAC™**

# SPECIFICATIONS



|                                             |                        | STMS8522T2         | STMS8522T3         | STMS8528T3         | STMS8530T3         |
|---------------------------------------------|------------------------|--------------------|--------------------|--------------------|--------------------|
| Body:                                       | Length                 | 22'0"              | 22'0"              | 28'0"              | 30'0"              |
|                                             | Width                  | 8'4"               | 8'4"               | 8'4"               | 8'4"               |
| Overall:                                    | Length                 | 24'9"              | 24'9"              | 30'9"              | 32'9"              |
|                                             | Width                  | 8'6"               | 8'6"               | 8'6"               | 8'6"               |
|                                             | Height                 | 9'2"               | 9'2"               | 9'2"               | 9'2"               |
| Interior:                                   | Length (including "V") | 21'8"              | 21'8"              | 27'8"              | 29'8"              |
|                                             | Width                  | 8'1"               | 8'1"               | 8'1"               | 8'1"               |
|                                             | Height                 | 7'0"               | 7'0"               | 7'0"               | 7'0"               |
| Width Between Wheel Boxes                   |                        | 83"                | 83"                | 83"                | 83"                |
| Platform Height                             |                        | 21"                | 21"                | 21"                | 21"                |
| Torflex® Suspension E-Z® Lube Axles:        | Qty<br>Type            | Tandem<br>45° Down | Tandem<br>45° Down | Tandem<br>45° Down | Tandem<br>45° Down |
| Electric Brakes with Breakaway Kit          |                        | Electric Drum      | Electric Drum      | Electric Drum      | Electric Drum      |
| Radial Tire Size<br>Tire Load Range         |                        | ST205/75R15<br>C   | ST225/75R15<br>D   | ST225/75R15<br>D   | ST225/75R15<br>D   |
| Hitch Ball Size                             |                        | 2-5/16"            | 2-5/16"            | 2-5/16"            | 2-5/16"            |
| Hitch Height to Top of Ball                 |                        | 23"                | 23"                | 23"                | 23"                |
| Hitch Weight (% of Curb Weight)             |                        | 10% to 15%         | 10% to 15%         | 10% to 15%         | 10% to 15%         |
| GVWR                                        |                        | 7,000 lb.          | 9,990 lb.          | 9,990 lb.          | 9,990 lb.          |
| Curb Weight (Approximate)                   |                        | 3,320 lb.          | 3,420 lb.          | 4,230 lb.          | 4,530 lb.          |
| Payload Capacity (Approximate)              |                        | 3,680 lb.          | 6,570 lb.          | 5,760 lb.          | 5,460 lb.          |
| Flush Lock Side Door Width - Width x Height |                        | 36" x 78"          | 36" x 78"          | 36" x 78"          | 36" x 78"          |
| Front Ramp Door Opening - Width x Height    |                        | 66" x 78"          | 66" x 78"          | 66" x 78"          | 66" x 78"          |
| Rear Ramp Door Opening - Width x Height     |                        | 94" x 80"          | 94" x 80"          | 94" x 80"          | 94" x 80"          |
| Beavertail Length                           |                        | 48"                | 48"                | 48"                | 48"                |
| 12v Male Connection                         |                        | 7-way              | 7-way              | 7-way              | 7-way              |

## STANDARD FEATURES

- 6' V-Front with Polished Aluminum Front Nose
- Mid-Deck Platform with Tapered Drive Over Wheel Boxes
- 94"W Rear Ramp Door with Spring Assist
- 48" Beavertail
- 66"W Front Ramp Door
- 36" Side Entry Door with Fold Down Steel Step (Road Side)
- 16" OC Floor Crossmembers
- 16" OC Tube Vertical Wall Posts
- 16" OC Tube Roof Framing
- 2000 lb. Front Wind Tongue Jack
- 3-Piece A-Frame
- Smooth Aluminum Fenderettes
- Torflex® Torsion Axles
- Radial Tires with Aluminum Wheels
- 3/4" PlexCore™ High-Performance Flooring
- White Vinyl Interior Sidewall Liner
- ATP Kickplate (12"H)
- 12v LED Interior Dome Lights (2) with Switch
- 12v LED Exterior Lighting Tail/Clearance Lights
- LED Rear ID Bar with Loading Light with Switch
- 1-Piece Aluminum Roof
- .080 ACP Panels (Select Colors)
- Flow-Thru Sidewall Vents
- 14in x 14in Non-Powered Roof Vent
- 5,000 lb. D-Rings (6)
- 24" ATP Stoneguard
- 14" x 14" Access/Fuel Door
- 3-Year Limited Warranty



Trailers shown may feature optional equipment available at additional cost.



[www.wellscargo.com](http://www.wellscargo.com)

Specifications, features, options, packages & pricing subject to change **without** notice. See your authorized Wells Cargo® dealer for more information.