

SILVERSPORT[®]

BY WELLS CARGO

ALL-ALUMINUM ENCLOSED UTILITY TRAILERS

**WELLS
CARGO[®]**



7' Wide

**Wells Cargo Engineered the SilverSport
to Exceed Your Performance Expectations**

STANDARD FEATURES

- Aluminum Frame
- V-Nose Profile
- 16" OC Tube Floor Crossmembers
- 16" OC Tube Wall Framing
- 16" OC Tube Roof Framing
- Square Tube 8K Dropleg Sidewide Jack with Footplate (Bolt-On/Replaceable)
- Adjustable Height 2-5/16" Wallace Forge[®] Cast Coupler (Made in the USA)
- Dexter Torflex[®] Torsion Axles
- Goodyear[®] Endurance Radial Tires
- Black Aluminum Wheels
- 36"W Side Entry Door w/ Flush Lock & Dead Bolt
- Choice of Rear Ramp or Double Doors
- All Aluminum "Anti-Rack" Cam Lock with Stainless Steel Hasp
- 3/4" PlexCore High-Performance Flooring
- 3/8" PlexCore High-Performance Wall Liner
- Rear ID Bar with Built-In Loading Light
- LED 12V Interior Lighting with Switch
- LED Exterior Lighting Tail/Clearance Lights
- Sidewall Vents
- 1-Piece Seamless Aluminum Roof
- .080 ACP Panels (Select Colors)
- 24" Stoneguard
- 3-Year Limited Warranty



8.5' Wide

www.wellscargo.com

Specifications, options & pricing subject to change without notice. See your authorized Wells Cargo dealer for more information.



ALL-ALUMINUM ENCLOSED UTILITY TRAILERS

Model		WSS714T2	WSS716T2	WSS8516T2	WSS8520T2	WSS8524T3
Body:	Length (Incl. "V")	17'0"	19'0"	19'0"	23'0"	27'0"
	Width	7'0"	7'0"	8'4"	8'4"	8'4"
Overall:	Length	19'1"	21'1"	21'1"	25'1"	29'1"
	Width	8'6"	8'6"	8'6"	8'6"	8'6"
	Height	8'4"	8'4"	8'6"	8'6"	8'6"
Interior:	Length	16'7"	18'7"	18'7"	22'7"	26'7"
	Width	6'9"	6'9"	8'1"	8'1"	8'1"
	Height	6'6"	6'6"	6'6"	6'6"	6'6"
Platform Height:		18"	18"	20"	20"	20"
Axle:	Quantity	Tandem	Tandem	Tandem	Tandem	Tandem
	Capacity	7,000 lbs.	7,000 lbs.	7,000 lbs.	7,000 lbs.	10,000 lbs.
	Type	10 ⁰ Up	10 ⁰ Up	10 ⁰ Up	10 ⁰ Up	10 ⁰ Up
	Suspension	Torflex®	Torflex®	Torflex®	Torflex®	Torflex®
	Brakes	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric
Tires:	Size	ST205/75R15	ST205/75R15	ST205/75R15	ST205/75R15	ST225/75R15
	Load Range	D	D	D	D	E
	Type	Goodyear® Radial	Goodyear® Radial	Goodyear® Radial	Goodyear® Radial	Goodyear® Radial
Wheels:		Black Aluminum	Black Aluminum	Black Aluminum	Black Aluminum	Black Aluminum
Hitch:	Ball Size	2-5/16"	2-5/16"	2-5/16"	2-5/16"	2-5/16"
	To Top of Ball	17" to 21"	17" to 21"	19" to 23"	19" to 23"	19" to 23"
	GVWR	7,000 lbs.	7,000 lbs.	7,000 lbs.	7,000 lbs.	9,990 lbs.
Rear Door:	Style	Ramp or Double Doors	Ramp or Double Doors	Ramp or Double Doors	Ramp or Double Doors	Ramp or Double Doors
	Width x Height	78" x 74"	78" x 74"	94" x 74"	93" x 74"	93" x 74"
	Hardware	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum
Side Door:	Width	36"	36"	36"	36"	36"
	Lock Style	Flush/Dead Bolt	Flush/Dead Bolt	Flush/Dead Bolt	Flush/Dead Bolt	Flush/Dead Bolt
Tube Main Rails:		2" x 4"	2" x 4"	2" x 6"	2" x 6"	2" x 6"
12V End Connector:		7-way	7-way	7-way	7-way	7-way
Stoneguard:		24"	24"	24"	24"	24"
Sidewall Vents:		STD	STD	STD	STD	STD
Interior Sidewall Liner:		3/8" PlexCore	3/8" PlexCore	3/8" PlexCore	3/8" PlexCore	3/8" PlexCore
Floor:		3/4" PlexCore	3/4" PlexCore	3/4" PlexCore	3/4" PlexCore	3/4" PlexCore